Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

RELIABILITY PREDICTION

Model : PT-65 Data:1999-12-30

Style	Part Type	Q'ty	λ_g	π_Q	λ_{eg}	%
9.1	Resistor-Film, Insulated (RL)	6	0.003700	10	0.222000	6.155
9.1	Resistor-Film, Chip (RM)	31	0.003700	10	1.147000	31.803
9.1	Resistor-Wirewound Power (RW)	1	0.008500	10	0.085000	2.357
9.1	Resistor-Film, Variable (RVC)	1	0.040000	10	0.400000	11.091
9.1	Resistor-Thermistor (RTH)	1	0.001400	10	0.014000	0.388
10.1	Capacitor-Metal, Plastic (CH)	3	0.000510	10	0.015300	0.424
10.1	Capacitor-Ceramic(Gen.) (CK)	18	0.001700	10	0.306000	8.484
10.1	Capacitor-Aluminum Dry (CE)	10	0.001300	10	0.130000	3.604
6.1	Diode-Gen. Purpose Analog	1	0.003600	8	0.028800	0.799
6.1	Diode-Switching	3	0.000940	8	0.022560	0.626
6.1	Diode-Fast Recovery Power Rectifier	2	0.023000	8	0.368000	10.203
6.1	Diode-Power Rectifier / Schottky Power	6	0.002800	8	0.134400	3.726
6.1	Diode-Voltage Ref/Reg. (Avalanche & Zener)	2	0.003300	8	0.052800	1.464
6.10	Diode-Thyristor/SCR	1	0.002500	8	0.020000	0.555
6.4	Transistor-MOSFET	1	0.014000	8	0.112000	3.105
5.1	Linear Microcircuits	5	0.009500	10	0.475000	13.170
11.1	Transformer Switching	1	0.000610	3	0.001830	0.051
11.2	Coil Fixed inductor or choke	3	0.000032	3	0.000288	0.008
17.1	Single Connections-Reflow solder	252	0.000069	1	0.017388	0.482
17.1	Fuses Clip-Clip Termination	2	0.000120	1	0.000240	0.007
22.1	Fuses	1	0.010000	1	0.010000	0.277
16.1	Plated Through Hole Circuit Boards	1	0.022000	2	0.044000	1.220
Total Failure rate:					3.606606	100%

- **Data Base: MIL-HDBK-217F ,Notice 2, Parts Count**
- **Env.: GB**

MTBF: 277268.99 **hrs**

Approved by: Compiled by: